



INTERNATIONAL JOURNAL OF ADVANCE RESEARCH, IDEAS AND INNOVATIONS IN TECHNOLOGY

ISSN: 2454-132X

Impact Factor: 6.078

(Volume 10, Issue 1 - V10I1-1173)

Available online at: <https://www.ijariit.com>

Self-compacting concrete

Zuber Shaikh

shaikh4264zuber@gmail.com

Bharati Vidyapeeth Institute of Technology,
Navi Mumbai, Maharashtra

Sujal Patil

sujalpatil0504@gmail.com

Bharati Vidyapeeth Institute of
Technology, Navi Mumbai, Maharashtra

Atharva Salvi

atharvasalvi143r@gmail.com

Bharati Vidyapeeth Institute of Technology,
Navi Mumbai, Maharashtra

Dharna Patil

dharnapatil29@gmail.com

Bharati Vidyapeeth Institute of Technology,
Navi Mumbai, Maharashtra

Nikhil Mishra

nikhilm662@gmail.com

Bharati Vidyapeeth Institute of
Technology, Navi Mumbai, Maharashtra

Sayali Patil

sayapatil11@gmail.com

Bharati Vidyapeeth Institute of Technology,
Navi Mumbai, Maharashtra

ABSTRACT

Self-compacting concrete (SCC) is a remarkable innovation in the field of construction materials. It represents a paradigm shift in the way concrete is designed and placed. This abstract provides an overview of self-compacting concrete, highlighting its properties, advantages, and applications. Self-compacting concrete is characterized by its unique ability to flow and fill intricate formwork under its own weight, without the need for external vibration. This remarkable property is achieved through a well-balanced mix design, incorporating high-flow ability materials, super plasticizers, and viscosity-modifying agents. SCC offers several significant advantages, including improved workability, reduced labor and equipment costs, enhanced structural integrity, and minimized environmental impact.

Keyword: Self Compacting Concrete, Highlights.

I. INTRODUCTION

With the huge increase in the construction of megastructures in the world, the demand for the use of self-compacting concrete (SCC) is also increasing. Many construction sites suffer from jamming of steel bars in large elements. Construction problems are further complicated by the high risk of seismic areas, vulnerability to storms and the increasing capacity of power plants. In a difficult environment, SCC became the only option. Ideally, the development of mixed concrete, where placement and compaction depend on existing working patterns at least in a particular area, should ensure the strength and therefore durability of the structure in the final structure. This is an important impetus for the development of self-compacting concrete (SCC).



Selfcompacting structure is considered a breakthrough in construction technology because it improves performance and the working environment. It has a wide range of applications, from thin products to large, complex designs. SCC is arguably the biggest technological advancement and most revolutionary development in concrete technology in recent years. SCC is the stone of the future as it will replace ordinary stone with its special quality.

Selfcompacting concrete (SCC), also known as selfcompacting concrete or rheological concrete, is an innovative concrete that does not require vibration while being poured and compacted. Even in the presence of a large number of steel rods, it can flow under its own weight, complete the mold and complete compression. Hardened concrete is thick, wearable, and just as engineered and durable as the material itself. The principle of selfcompacting concrete (SCC) is that the slump of aggregates depends on the viscosity of the new concrete. SCC can be produced using the same components as regular concrete. However, more stringent measures must be taken to ensure strict control of the work product. SCC mixing ratio is more scientific than standard mixing ratio. SCC mix should have high powder content, small amount of coarse aggregate, superplasticizer and VMA (viscosity modifier) for the stability and fluidity of the concrete mix. The SCC process is a balance of fluidity, deformability, filling and separation resistance. This balance must be maintained for a sufficient period of time to allow transportation and placement.

II. PROJECT OBJECTIVES

This section aims to provide information to designers, developers, manufacturers, and users who want to improve their experience and use of SCC. It will provide useful advice to professionals and contractors working in water utilities and public works. The instructions in this section contain general information for SCC ready-mix, field-mixed concrete.

The guide has been developed with a focus on readymix, integrated SCC that includes requirements associated with ruggedized case specifications. Additionally, the guidelines contain specific and important requirements for SCC users regarding site preparation for vibrated concrete.

This document describes the properties of SCC in its new and hardened states and provides recommendations for users of composite materials on how to gain a good understanding of mixing, SCC properties. Advise developers about devices, their controls and interactions.

Since there are many ways to create SCC composites, there is no single recommended way. However, a hybrid design method is provided. Advising mix preparation contractors/clients on delivery and placement of field mix to SCC.

III. METHODOLOGY

Material selection:

Using quality materials, including quality aggregates, aggregates, cement and chemical products. Use appropriate additives to improve product integrity and reduce the risk of separation.

Mix Design: Design the mix to ensure that the concrete achieves the desired fluidity and stability. The proportions of fine and coarse aggregate, water and additives are adjusted to obtain the desired rheological properties.

Additives: Add high efficiency water reducing admixtures or high efficiency water reducing admixtures to improve the workability of concrete without increasing the water content.

Water-Cement Ratio: Keep the watercement ratio low to maintain the strength of the concrete while achieving the desired flow.

Testing and Quality Control: Many tests are performed to evaluate the new and hardened properties of concrete. Adjust the mix design as needed based on test results.

Pouring:

Place the selfcompacting concrete into the mold without external vibration, ensure that the concrete flows completely and completely into the mold.

Curing: Monitor the curing process to encourage the development of concrete to make it stronger and longer-lasting.

IV. FUTURE SCOPE AND APPLICATION

This section aims to provide information to designers, developers, manufacturers, and users who want to improve their experience and use of SCC. It will serve as a useful guide for professionals and contractors working in water utilities and public works. The guidance in this section contains general information about SCC in mix planning and site mix construction. These guidelines were developed with a particular focus on ready-mix, field mixed SCC for concrete requirements. province.

Additionally, the guidelines contain specific and important requirements for SCC users regarding site preparation for vibrated concrete. This document describes the properties of SCC in both its fresh and hardened states and provides recommendations to users of composites on how to determine combinations of SCC. Advise developers about devices, their controls and interactions. Since there are many different methods available for the design of SCC composites, no specific method is recommended. However, a hybrid design method is provided. Provide contractors/clients with mix preparation, SCC mixing instructions during delivery and placement.

V. NECESSITY OF SCC

SCC is considered the first choice due to its good fluidity, permeability and compatibility. SCC is an excellent concrete material due to its ability to flow through narrow openings. Since repair work requires a connection between old and new concrete, care should be taken to prevent shrinkage of the concrete by adding shrinkage compensating additives. It is necessary to squeeze steel bars, pour the second level concrete into the door cavity, and use SCC throughout the shape of the concrete.

VI. CONCLUSION

Selfcompacting concrete (SCC) is a gamechanging material for the construction industry. Its quality, efficiency, diversity and other features make it an important element of modern architecture. SCC not only simplifies construction but also improves integrity and durability, making it an important choice in many applications.

In order to show the competition for a beautiful face, SCC proposed competition in which there is no competition, the frame is not matched with narrow and dense areas. Since procedures for SCC do not exist in institutions and facilities, SCC components must be developed through trial and error.

Since the service life of MIS is shorter and its cost is cheaper than ordinary concrete, it is recommended to use SCC in high-rise buildings. SCC has been tested 14 times and its main components are superplasticizer, VMA and fine materials (cement and fly ash) that play an important role in SCC performance. SCC is based on not just one test but four tests, all of which must be taken into account for self-compacting concrete.

VII. ACKNOWLEDGEMENT

It gives me immense pleasure to present my Synopsis Report on “SELF COMPACTING CONCRETE” and to express my deep regards towards those who have offered their valuable time and guidance in my hour of need. I would like to express my sincere and whole-hearted thanks to my project guide Mrs. Sayali Patil and Head of Department Mrs. Cissy Shaji for contributing their valuable time, knowledge, experience and guidance in making this project successfully done. I am also glad to express my gratitude and thanks to my college Bharati Vidyapeeth Institute of Technology, Navi Mumbai and Respected Principal Mr. P.N. Tandon for continuous inspiration and encouragement. This report helped me to learn new techniques, developments taking place in Civil Engineering and to revise some previous concepts. Indeed, I perceive this opportunity as a milestone in my career development. Last but not the least, I sincerely thank to my colleagues, the staff and all others who directly or indirectly helped me and made numerous suggestions which have surely improved the quality of my work

VIII. REFERENCE

- [1] Bui, V.K.; Montgomery, D.; Hinczak, I. and Turner, K. (2002).Rapid testing method for segregation resistance of self-compacting concrete.Cement and Concrete Research. 32: 1489-1496.
- [2] Cengiz, Duran Aity (2005). Strength properties of high- volume fly ash roller compacted and workable concrete and influence of curing condition. Cement and Concrete Research. 35: 1112-1121.
- [3] Domone, P. and His- Wen, C (1997).Testing of binders for high performance concrete research.Cement and Concrete Research.27: 1141- 1147.
- [4] Domone, P. (2007). A review of the hardened mechanical properties of self- compacting concrete.Cement and Concrete Composites. 29: 1-12.
- [5] Ferrara, Liberato; Park, Yong- Dong and Shah, Surendra P. (2006).A method for mix design of fibre reinforced self-compacting concrete. Cement and Concrete Research. 37: 957971.
- [6] Grdić, Zoran; Despotović, Iva and TopličićĆurčić, Gordana (2008).Properties of self- compacting concrete with different types of additives. Architecture and Civil Engineering. Volume 6, No. 2: 173-174.

- [7] Heba, A. Mohamed (2011).Effect of fly ash and silica fume on compressive strength of self- compacting concrete under different curing conditions.Ain Shams Engineering Journal. 2: 79-86.
- [8] Khatib, J.M. (2008). Performance of self- compacting concrete containing fly ash.Construction and Building Materials. 22: 1963-1971.
- [9] Kumar, P.(2006).Methods of testing and design. IE (I) Journal- CV, Volume 86: 145-150.
- [10]Lachemi, M and Hossain, K.M.A. (2004). Self- consolidating concrete incorporating new viscosity modifying admixtures. Cement and Concrete Research. 34: 917-